

RED ALERT® Series, WiFi VoIP Emergency Telephones - Model 397-811A

By GAI-Tronics
Catalog # 397-811A

RED ALERT WiFi VoIP Flush-Mount Emergency Telephone, "HELP" Button & One Auto-dial button



Features

- 24-48 V dc Supply
- SIP Compatible
- Four Inputs and Two Outputs Per Phone
- Auto Answer
- Multicast Capable (Up to 8 Addresses)

Application

Emerg. Telephone Comm., wireless (campuses, parking lots, paths)

Specifications

Certified Listed	UL/CSA/FCC
Certification	UL/CSA/FCC
Compliance	FCC CRF 47 Part 15
Weather Rating	Type 3R

Configuration

Mount location	Flush-Mount
----------------	-------------

Current

Signal	WiFi
Voltage Rating Description	24-48 VDC

Dimensions

Width	10.0 in
Weight	7.2 lb.

Height	12.0 in
Dimensions Shipping	16.5 x 16.0 x 10.0
Length	2.38 in
Dimensions	2.38 in x 10.0 in x 12.0 in

General

Construction	<ul style="list-style-type: none"> • Front Panel: 14-Gauge Type 304 Brushed Stainless Steel • Dust Cover: 16-Gauge Cold-Rolled Steel With Black Polyurethane Finish
Type	<ul style="list-style-type: none"> • Emergency Telephones • HELP Button & Auto-Dial
Series	RED ALERT® Series
Signal Type	VoIP - SIP
Material type	Stainless Steel
Specifications	UL/CSA, FCC
Color	Silver

Operational

Storage Temperature Range	-40° C to +70° C
Temperature Rating	-4°F to +131°F (-20°C to +55°C)
Operating Temperature	-4°F to +131°F / -20°C to +55°C
Connectivity Options	WiFi VoIP
Output Level Speaker	87 dB @ 1 M

Product Assets

[Installation Manual \[English\]](#)