DATA SHEET

COD. HFX-700R

REVISION N°11 - 11/08/2011

HANDS-FREE EXPANDABLE VIDEO INTERCOM KIT WITH RECORDING ABILITY AND DIGITAL PTZ

Hands free color expandable video intercom kit w/ audio video. memory recording on a micro SD Card (SD Card not included). Includes. master monitor, door bell and power supply. Expandable up to 2 door. stations and 4 monitors. (up to 8 monitor stations with 2 EX-HUBs). - Expandable up to 8 monitors and 2 Door Camera stations - Simple 2 Wire installation - 3.5" LCD Monitor - "All-Page" Communication between monitors - 1/3" CCD Chipset - Camera angle vertically adjustable - manually - White LED illuminator in low lighting conditions - Weather resistant plastic door bell housing - Remote door release (12VDC or NO Dry Contact) - Adjustable speaker, mic and chime volume - Power: 24VDC 650mA





Mounting/Installation

Flush-mounted:	optional (EX-700V)	
Wall-mounted:	Yes	
Desk base-mounted:	optional (CDSK)	
Surface-mounted:	Standard for door camera and monitor	
DIN rail mounted:	No	
DIN modules (no.):	No	

Audio/video specifications

B/W or colour display:	Color
OSD display:	Touch Sensitive
Digital zoom:	Yes

Hardware specifications

Dry contact for fault signalling:	Magnetic contact terminals
SD memory card:	Micro-SD Card Slot

Connectivity

Type of connections/ports: 2 wire connection (singal)

Functions - Settings

Intercom function:	All-Page Intercom
Privacy function:	Yes
PTZ management:	Digital

Electrical specifications

AC supply voltage:	110/240 50/60 Hz
Direct voltage output A (V):	12VDC 300mA



DATA SHEET

Maximum current absorption (mA):	23VDC/1A
eral info	
Self-ignition:	Yes
EAN product code:	8023903232431
Type of finish:	Plastic
Product height (mm):	7.0'
Product width (mm):	4.65'
Product depth (mm):	1.42'
Product weight:	1 LBS
Unit of measurement:	Inches
Product colour:	White
aging	
Single pack quantity (no.):	1

