

MOOD:

MULTI-PURPOSE SPEAKERS

Mood, the most trusted name in commercial sound systems, systems integration and installations, introduces its professional speaker series ensuring a quality experience from source to sound. With our expertise in how music, imaging, messaging and systems work in high-traffic business environments, we've designed flexible speaker systems that enhance playback with unbeatable sound quality.

MOOD MULTIPURPOSE SPEAKERS OFFER

- + Superior Fidelity
- + High Aesthetic Appeal
- + Dependability
- + Quick and Easy Installation
- + Competitive Pricing
- + 8 Ohm Thru
- + "C" Style Mounting Bracket Included

MOOD SM SERIES The SM line includes two types of ultra-compact, wall-mount loudspeakers. With excellent bass response, extended bandwidth and superb musicality, the SM series works to eliminate distortion while delivering a smooth, clear sound. Constructed to maximize speaker efficiency, the SM series allows your music to sound fuller at lower volumes.

Mood SM105 - 5.25" Surface Mount Speaker



Mood SM104 - 4" Surface Mount Speaker



SM104 SPECIFICATIONS

FREQUENCY RESPONSE:	90 Hz-18 kHz
POWER HANDLING:	35 watts RMS
SENSITIVITY:	88 dB
NOMINAL IMPEDANCE:	8 ohms
70 VOLT WATTAGE TAPS:	.625,1.25,2.5,5,10
100 VOLT WATTAGE TAPS:	1.25,2.5,5,10
CROSSOVER FREQUENCY:	3 kHz
DIMENSIONS:	WxHxD 5.5" x 8" x 4.9"
WEIGHT:	3.75 lbs.
COLORS:	Available in black or white

NOTE: This speaker is rated outdoor for indirect exposure.

SM105 SPECIFICATIONS

FREQUENCY RESPONSE:	75 Hz-18 kHz
POWER HANDLING:	50 watts RMS
SENSITIVITY:	88 dB
NOMINAL IMPEDANCE:	8 ohms
70 VOLT WATTAGE TAPS:	1.25,2.5,5,7.5,15
100 VOLT WATTAGE TAPS:	2.5,5,10,15
CROSSOVER FREQUENCY:	3 kHz
DIMENSIONS:	WxHxD 8.3"x11.1"x7.5"
WEIGHT:	5.42 lbs.
COLORS:	Available in black or white

NOTE: This speaker is rated outdoor for indirect exposure.

MOOD:

CM SERIES FLUSH MOUNT SPEAKERS

CM1525R and CM6201T speakers are 9.25" and 10.25" in diameter respectively



The Mood CM Series flush-mount speakers are tuned to deliver optimum low and high frequencies for a truly precise and balanced soundstage. The CM design ensures extended yet accurate bass response, smooth mid-range response and extended high-frequency response to create a lifelike musical experience.

FEATURES

- + .04" drawn steel enclosure
- + Bass reflex
- + ABS baffle
- + Paintable grille
- + Easy installation, new and retrofit
- + 70/100 volt transformer
- + 8 Ohm Thru
- + Tile Support Included
- + UL 1480 Listed

CM1525R SPECIFICATIONS

FREQUENCY RESPONSE:	80 Hz-18 kHz
POWER HANDLING:	20 watts RMS
SENSITIVITY:	88 dB
NOMINAL IMPEDANCE:	8 ohms
70 VOLT WATTAGE TAPS:	.625,1.25,2.5,5,10
100 VOLT WATTAGE TAPS:	1.25,2.5,5,10
LF DRIVER:	5.25" PP cone, butyl rubber surround
HF DRIVER:	.5" sealed ferrofluid soft dome, NeFeB magnet
CROSSOVER FREQUENCY:	3 kHz
DIMENSIONS:	9.25" diameter x 7" deep
WEIGHT:	5.21 lbs.
COLORS:	White only
CUTOUT SIZE:	8.11"

CM6201T SPECIFICATIONS

FREQUENCY RESPONSE:	60 Hz - 20 kHz
POWER HANDLING:	20 watts RMS
SENSITIVITY:	89dB, 1 watt, 1 meter
NOMINAL IMPEDANCE:	8 ohms
70 VOLT WATTAGE TAPS:	1.9, 3.7, 7.5, 15, 30
100 VOLT WATTAGE TAPS:	3.8, 7.5, 15, 30
LF DRIVER:	6.5" PP cone, butyl rubber surround
HF DRIVER:	.75" sealed ferrofluid soft dome, NeFeB magnet
CROSSOVER FREQUENCY:	6 kHz first order
DIMENSIONS:	10.24" diam. x 7.4" deep
WEIGHT:	7.71 lbs.
COLORS:	White only
CUTOUT SIZE:	9.05"