

# UNIVERGE® SV9300

## COMMUNICATIONS PLATFORM

The UNIVERGE® SV9300 unified communications solution is a robust, feature-rich system that is ideal for geographically distributed businesses and enterprises. It is designed to help solve today's communications and collaboration challenges and offers easy integration with NEC's unique vertical solutions.



### UNIVERGE® SV9300 AT A GLANCE

- > 2U 19-inch rack high-availability Appliance Server with redundant power, network ports and Intel® Core CPU Options
- > IP networked geographical redundancy with alternative MGC's
- > Multi-Line SIP Client and multiple SIP carrier support
- > Wide-range of endpoints for all IP extensions/digital/analog
- > Seamless and flexible deployment with up to 1,536 IP extensions in one system
- > Hospitality feature options
- > Global regulatory and environmental compliances including FCC, UL/CSA, CE Marking, Industry Canada, RoHS, REACH and Section 508 Compliant

### THE SV9300 OFFERS

## SMART COMMUNICATIONS FOR SMALL AND MEDIUM BUSINESSES



### CUSTOMIZABLE FOR SPECIFIC REQUIREMENTS

The SV9300 communications platform offers:

- > Powerful Unified Communications with Mobility and Unified Messaging integrated within the solution
- > Streamlined application integration through the new simplified user licensing structure
- > Easy-to-use single point configuration and management
- > 19-inch stackable chassis architecture which supports server functions, media gateways and media converters in a single unit

**TECHNICAL DATA**

		1 Unit			2 Units	3 Units	4 Units	System Max.				
		2U x 1	2U x 2	2U x 3	2U x 6	2U x 9	2U x 12	Standalone	Remote Unit			
<b>Blade Slots</b>		6	12	18	36	54	72	72	900			
<b>Port</b>	Physical Port	108	216	324	648	972	1296	1296	2048	2048	2048	
	Virtual Port	1536			2048			2048		2048		
<b>Physical Port</b>	SLT (-28V)	96	192	288	576	864	1152	1152	1536	1536	1536	
	SLT (-48V)	24	48	72	144	216	288	288		1536		
	Digital Multiline Terminal (-48V)	96	192	288	576	864	1152	1152		1536		
	Digital Multiline Terminal (-48V) w/APR (Note 1)	28	56	84	168	252	336	336		768		(768)
	DSS Console (Note 2)	32						32		32		32
	Desk Console (Note 4)	8						8		8		8
	ISDN Terminal (BRI Bch) (Note 3)	48	96	144	256			256		256		256
	In-skin UMS Port	48	96	128				128		128		128
	16-Party Conference w/ PVA (ch)	96	128							128		128
<b>Virtual Port</b>	IP Multiline Terminal	1024			1536			1536	1536	1536		
	Softphone											
	Wi-Fi Handset											
	IP Single Line Telephone (SIP) (Standard SIP Terminal)	512			1024			1024		1024		
	DSS Console (Note 2)	32						32		32		
<b>Physical Port</b>	Central	COT	48	96	144	288	432	512	512	512	512	
	Office Trunk	DID	24	48	72	144	216	288	288	512		
	Tie Line Trunk	E&M	24	48	72	144	216	288	288	512		
	BRI Trunk (Note 3)		48	96	144	256			256	256		
	PRI Trunk (Note 6)	23B+D	96	192	288	504			504	504		
		30B+D	93	186	279	496			496	496		
	DTI Trunk	T1	96	192	288	504			504	504		
		E1	90	180	270	510			510	510		
	CCIS Trunk (Note 6)	1.5M	96	192	288	384			384	384		
	2M	93	186	279	496			496	496			
<b>Virtual Port</b>	IP Trunk (P2P CCIS)	512						512	512			
	SIP Trunk (Note 8)	100			200	300	400	400	512			
<b>VoIP Channel</b>	w/ RTP	128			256	384	512	512	6400			
<b>SIP Converter</b>		96			192	288	384	384	384			
<b>Modem Channel</b> (Note 4)		1						1	1			
<b>Speech Synthesis announcement</b> (Note 4)		8						8	8	16		
<b>VRS Message</b> (Note 4)		16						16	16	16		
<b>DTMF Sender</b>		64						64	64			
<b>Caller ID Sender (FSK)</b>		16						16	16			
<b>DTMF Receiver</b> (Note 5)		32						32	32	32		
<b>MF Sender</b> (Note 4, 5)		32						32	32			
<b>MF Receiver</b> (Note 5)		32						32	32			
<b>Caller ID Receiver (FSK)</b> (Note 5)		32						32	32			
<b>Caller ID Receiver (DTMF)</b> (Note 5)		32						32	32			
<b>MFC Sender</b> (Note 5)		16						16	16			
<b>MFC Receiver</b> (Note 5)		16						16	16			
<b>3-/4-Party Conference (ch)</b>		64			128			128	128		128	
<b>32-Party Conference (ch)</b> (Note 7)		32						32	32	128		

Note 1: When using a D<sup>term</sup> with APR (Dual Port Mode), the physical ports for analog station shown in parenthesis are required in addition to the physical ports for Multiline Terminal.  
 Note 2: The total number of following DSS Consoles is maximum 32 per system. Note 3: The required number of ports per blade is shown in Table 4-2. (e.g. GCD-2BRIA +GPZ-2BRIA: 8 ports)  
 Note 4: Available at main unit (Unit01) only. Note 5: The total number of following functions is maximum 32 per system. DTMF Receiver, Caller ID Receiver (FSK), Caller ID Receiver (DTMF), MFC Sender, MFC Receiver, MF Sender, MF Receiver, Note 6: The number of System Port Capacity Licenses required is different from the number of actual Physical Ports consumed. Refer to Table 8-2. Note 7: The following conference groups can be configured. One, 32-party conference group, Two, 16-party conference groups, Four, eight-party conference groups Note 8: In case of call from/to TDM terminal via SIP trunk, maximum 512 calls (100 calls per unit) can be established at the same time, because one VoIPDB channel is occupied per call. In case of call from/to IP terminal via SIP trunk, maximum 50 calls can be established at the same time, because two VoIPDB channels are occupied per call.

NEC and the NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All trademarks identified with © or TM are registered trademarks or trademarks of their respective owners. Models may vary for each country, and due to continuous improvements this specification is subject to change without notice. Please refer to your local NEC representative(s) for further details.

**Americas (U.S., Canada, Latin America)**  
 NEC Corporation of America  
[www.necam.com](http://www.necam.com)

For further information please contact NEC Corporation of America or: