



APC Smart-UPS X 3000VA Rack/Tower LCD 100-127V

SMX3000RMLV2U

In Stock

\$1,750.00*

- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
- Includes: CD with software, Documentation CD, Installation guide, Rack Mounting brackets, Rack mounting hardware, Rack Mounting support rails, Removable support feet, Smart UPS signalling RS-232 cable, USB cable

Output	
Output power capacity	2.7kWatts / 2.88kVA
Max Configurable Power (Watts)	2.7kWatts / 2.88kVA
Nominal Output Voltage	120V
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	100, 110, 127
Topology	Line Interactive
Waveform type	Sine wave
Output Connections	(3) NEMA 5-15R (Battery Backup) (3) NEMA 5-20R (Battery Backup) (1) NEMA L5-30R (Battery Backup)
Transfer Time	2-4 ms 4ms typical : 8ms maximum


Input	
Nominal Input Voltage	120V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	NEMA L5-30P
Cord Length	8ft (2.44meters)
Input voltage range for main operations	70 - 153V
Number of Power Cords	1
Other Input Voltages	100, 110, 127

*Prices are indicative

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

Input	
Transfer Time	2-4 ms

Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)
Replacement Battery	APCRBC117 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Extendable Run Time	1
Extended Run Options	APC-Smart-UPS-X-3000VA-Rack-Tower-LCD-100-127V (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	SmartSlot, USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators, Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	540Joules
Data Line Protection	--
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical	
Maximum Height	3.36inches (85MM, 8.5CM)
Maximum Width	17.0inches (432MM, 43.2CM)
Maximum Depth	26.26inches (667MM, 66.7CM)

*Prices are indicative

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

Physical	
Rack Height	2U
Net Weight	84.6lbs. (38.45KG)
Shipping weight	99.79lbs. (45.36KG)
Shipping Height	9.58inches (243MM, 24.3CM)
Shipping Width	23.48inches (596MM, 59.6CM)
Shipping Depth	34.23inches (869MM, 86.9CM)
Color	Black
Pallet Dimensions	39.369999999999997inches
# of Layers per Pallet	4.0
# of Units per Layer per Pallet	2.0
Pallet Weight	855.12lbs.
Units per Pallet	8.0

Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000ft (0-15000meters)
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	276.0BTU/hr

Conformance	
Approvals	BSMI, CSA, EN 50091-2, EN 55022 Class A, FCC Part 15 Class A, NOM, TUV, UL 1778, VCCI Class A
Equipment protection policy	Lifetime : \$150000
Standard warranty	3 years repair or replace (excluding battery) and 2 year for battery, optional on-site warranties available, optional extended warranties available

*Prices are indicative

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC Smart-UPS X 3000VA Rack/Tower LCD 100-127V | SMX3000RMLV2U | Downloaded on 08/01/2019 (EST)

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOLI	Available in Documentation tab
Proposition 65 Warning	Available in Documentation tab

*Prices are indicative

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.