# 360° PUBLIC ADDRESS FOR 1 AND 5 SERIES









# **Product Description**

The 360° Public Address System for 1 and 5 Series Help Points® from Code Blue is exclusively designed as an emergency communication system to deliver maximum audio clarity and range to ensure notifications are accurately broadcast to your intended audience. The unique 6-speaker design delivers optimal audio source dispersion utilizing stateof-the-art amplifiers and horn array.

### **Standard Features**

- Proprietary One-Cycle Sound™ control w/ output feedback
- ✓ Internal and remote volume adjustment
- ✓ Synchronized switching frequencies
- ✓ FXS, IP or no analog controller
- ✓ Remote disable
- Temperature, output and clipping signal self-monitoring
- Full over current, under voltage and over temperature protection
- Standard and custom paint and graphics available

### **Popular Upgrades**


**Fusion Server** 



#### **Blue Alert® MNS**



# **Optimal Sound Dispersion**



















# **Technical Features**

#### Available for the:

- CB 1-e
- CB 1-s
- CB 5-s

### **Specifications**

Height: 19.36" (49.17 cm)Width: 14.05" (35.69 cm)

• Weight: 25 lbs. (11.34 kg)

• Speakers: 6

• Dispersion Angle: 360°

 Material: Acrylonitrile Butadiene Styrene (ABS)

• **Power:** 120V AC



 Frequency Response: 450Hz-7kHz

Power Capacity: 420w continuous program

• Impedance: 5.3 Ohms

## **Amplifier**

 Output Power: 400w (20Hz-20kHz, 0.1% THD)

 Maximum Output Power: 500w (1%THD)

 Max Bridged Output Power: 500w (1% THD)

• Sensitivity: 3.5 Vrms

Distortion: 0.05% (0.03% average)

Frequency Response:
 20Hz-20kHz, ±0.5dB

Signal to Noise: 117dB





- Standard wet coat colors: Dark Bronze, Gloss White, Gloss Black, Safety Blue, Safety Red, Safety Yellow, Bright Silver
- Custom colors available




- UL 2017
- IP56
- Built to NEMA 4
  Specifications









CB 1-s with Public Address

Note: Specifications subject to change without notice or obligation on the part of Code Blue Corporation.









