

Technical Specifications

V-1015B Pendent Speaker

- One-way paging
- Omni-directional mounting
- High-fidelity full range speaker
- Quick and easy installation
- Available in black (-BK), gray (-GY) or white (-W)
high gloss finishes
- Indoor use only



*Self-amplified one-way
5-Watt*

Description:

The V-1015B 5-Watt One-Way Pendent Speaker is a low-profile tube style speaker for areas with high ceiling heights that require an upscale contemporary appearance. The contemporary look blends well with modern architecture and is ideal for airports, retail stores, shopping malls, restaurants, offices, hallways, and covered patios where intelligible speech and music is needed. The V-1015B includes a six-foot black steel chain which easily attaches to the top of the speaker and allows it to hang in a suspended fashion.

SPECIFICATIONS

SPEAKER ELEMENT

Cone Diameter: 5.00in (12.70cm)
Voice Coil Impedance: 8 Ohms

INPUT

Impedance: > 600 Ohms nominal
Signal Level: -10 dBm line level

OUTPUT

Rating: > 100 dB @ 4ft (1.22m)

POWER REQUIREMENTS

300 mA @ -24 Vdc

FREQUENCY RESPONSE

70 Hz to 16 kHz

MAGNET

Cone type with 5oz (142g) ceramic magnet

ENVIRONMENT

Temperature: -4 to +131°F (-20 to +55°C)
Humidity: 0 to 95% non-condensing

HOUSING AND FINISH

Aluminum tube construction with white, black or gray powder coat finish. A 6-foot chain with black finish is included for hanging the speaker.

DIMENSIONS AND WEIGHT

8.80in L x 5.80in Dia
(22.35cm x 14.73cm)
Weight: 3.20lbs (1.44kg)
Shipping Weight: 7.60lbs (3.42kg)

2022 Rev. 7.7.18

Technical Specifications

ARCHITECTS AND ENGINEERS

The Pendent Speaker, model V-1015B, shall include a speaker, amplifier, externally accessible volume controls and a 6-foot steel chain.

The V-1015B Pendent Speaker frequency response shall be 70 Hz to 16 kHz. The output shall be 100 dB at 4ft (1.22m).

The V-1015B Pendent Speaker amplifier shall operate on a -24 Vdc nominal, positive ground power supply. Operating current shall be 300 mA at -24 Vdc. Operating temperature shall be -4 to +131 °F (-20 to +55 °C). Humidity range shall be 0-95%, non-condensing.

The V-1015B Pendent Speaker shall be constructed of aluminum tubing and finished in white, gray or black epoxy powder coat paint. A 6-foot chain with a black finish shall be included for hanging the speaker. The V-1015B speaker shall have an externally accessible volume controls that is adjustable by a screwdriver through the hole in the grille. V-1015B shall be suitable for indoor applications.

The maximum dimensions shall be: 8.80in L x 5.80in Dia (22.35cm x 14.73cm) . Weight shall be approximately: 3.20lbs (1.44kg)

Warranty information may be found on our website at www.valcom.com/warranty.