

Technical Specifications

VL550F-IC InformaCast® IP Text Sign with Speaker and Flashers

- InformaCast® compliant
- ADA compliant
- Easy to read multi color LED display
- SIP enabled
- Dual flashers
- PoE for simple installation
- Paging, intercom, clock, visual messaging and emergency alerts
- High quality audio with software volume control
- ShakeAlert® compatible
- Call switch inputs quality
- Quick and easy installation
- Available in black (VL550BK-F-IC), metallic (VL550M-F-IC)
- Indoor use only



*InformaCast® compliant
40-inch wide
dual side mounted flashers*

Description:

The VL550F-IC InformaCast® IP Text Sign with Speaker and Flashers provides high quality voice paging, intercom, clock and customizable visual notification in an All-In-One IP Endpoint. Perfect choice for indoor spaces such as cafeterias, auditoriums, gymnasiums, waiting areas and conference rooms.

SPECIFICATIONS

AUDIO OUTPUT

Rating: > 96 dB @ 4ft (1.22 m)

Signal/noise ratio: -70

FREQUENCY RESPONSE

80 Hz to 15 kHz

AUDIO CODECS

G.711 u-law, others

AUXILIARY RELAYS

Form C Relay rated at 1A @ 24 Vdc

POWER REQUIREMENTS

802.3at (Power over Ethernet+ PoE Plus) Class 4

PROTOCOLS

IETF SIP (RFC3261)

IETF IGMP version 2 or 3 (RFC2236, RFC3376)

IETF RTP (RFC1889)

IETF RTP Payload for DTMF (RFC2833)

NETWORK

10/100 Mbps Ethernet

Manual or Dynamic Host Configuration Protocol (DHCP) IP address assignment.

Time and date synchronization using NTP

INFORMACAST CONFIGURATION METHODS

SLP (Service Location Protocol)

Static Configuration

ENVIRONMENT

Temperature: +32 to +131 °F (0 to +40 °C)

Humidity: 0 to 85% non-precipitating

HOUSING AND FINISH

Aluminum case with black or metallic finish

DIMENSIONS AND WEIGHT

41.75in L x 5.88in H x 3.00in D (top) 2.50in D (bottom)
(106.00cm x 14.90cm x 7.60cm (top) x 6.40cm (bottom)

Weight: 9.20lbs (4.20kg)

Shipping Weight: 14.00lbs (6.30kg)

2022 Rev. 1.9.4

Technical Specifications

ARCHITECTS AND ENGINEERS

The IP Text Sign with Speaker and Flashers, model VL550F-IC, shall be InformaCast® compliant. The VL550F-IC shall provide highly visible message output and voice paging over an Ethernet network. Messages are created and delivered from the InformaCast® server.

The VL550F-IC IP Text Sign with Speaker and Flashers shall consist of high efficiency speaker, high visibility message display, and dual flashers. Speaker output and LED display can be activated together or separately. Display can operate as a clock, or provide other message during idle periods.

Power is provided to the VL550F-IC via a Power over Ethernet (PoE) switch meeting the 802.3af specification. Setup of the VL550F-IC shall automatically acquire an IP address (using DHCP) and connect

to the InformaCast® server when connected to the network and powered up. Information specific to the application shall need to be programmed into the InformaCast® server.

The VL550F-IC IP Text Sign with Speaker and Flashers case shall be constructed of aluminum with black or metallic finish. The VL550F-IC shall be suitable for indoor applications.

The maximum dimensions shall be: 41.75in L x 5.88in H x 3.00in D (Top), 2.50in D (Bottom) (106.00cm x 14.90cm x 7.60cm (top) x 6.40cm (Bottom). Weight shall be approximately: 9.20lbs (4.20kg).

Warranty information may be found on our website at www.valcom.com/warranty.